ST STACKERS

HIGH PERFORMANCE STACKERS

The McCloskey™ ST TRACKED Stackers are all about efficiency, from its speedy setup time to its high degree of mobility, downtime is minimized while throughput and stockpile capacity are maximized.

Hydraulic main lift and top fold are standard, as is the diesel power unit. Electric and dual power are also available to get the job done, no matter what application. The 22.5 degree maximum conveyor angle allows for the highest stockpiles per conveyor length in the industry.

With its durable truss frame, large feed hopper and base production capacity of 500 TPH with optional upgrades to 800 TPH, the McCloskey ST TRACKED Stackers stand up well above the competition.

ST80T

RADIO REMOTE TRACK CONTROL
Provides remote maneuverability and enhances safety for moving freely to the best location.

HYDRAULIC TOP FOLD
Straightforward hydraulic controls to fold and unfold, raise and lower the conveyor.

HEAVY DUTY BELT
Conveyor built with Heavy Duty 36” - 3 ply- belt.

OPTIONAL V-BIN
Higher capacity over 7 yds³ V-Bin hopper allows for larger amounts of material to be directly loaded into the hopper with a loader or excavator and comes fitted with stabilizer legs.

OPTIONAL PADDLE WHEEL
This unit attaches to the top end of the head frame of the stacker and helps to mix material as it discharges from the conveyor.

OPTIONAL AUXILIARY GUARDING
This option attaches to the sides of the tail frame and improves safety by limiting exposure to moving parts.

OPTIONAL MAGNETIC SEPARATOR
This high powered magnet/conveyor combination attaches to the tail frame of the stacker and enables magnetic material separation from the source material.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.

©Copyright 2019 McCloskey International. All rights reserved.
McCloskey is a trademark of McCloskey International.

McCloskey INTERNATIONAL

ST80T

Engine	Diesel or Electric
Transport Length	51’ 4” (15.6m)
Transport Height	13’ 2” (4.0m)
Transport Width	8’ 5” (2.6 m)
Stockpile Height	31’ 1” (9.47m)
Belt	36” x 80’ (900mm x 24.4m)
Production	500 US TPH

ST80TV

Engine	Diesel or Electric
Transport Length	52’ (15.9m)
Transport Height	11’ 4” (3.4m)
Transport Width	8’ 5” (2.6 m)
Stockpile Height	31’ 1” (9.47m)
Belt	36” x 80’ (900mm x 24.4m)
Production	800 US TPH

ST100T

Engine	Diesel or Electric
Transport Length	70’ 6” (21.5m)
Transport Height	13’ 6” (4.1m)
Transport Width	8’ 5” (2.6 m)
Stockpile Height	41’ 3” (12.5m)
Belt	36” x 100’ (900mm x 30.9m)
Production	500 US TPH

ST100TV

Engine	Diesel or Electric
Transport Length	70’ 4” (21.4m)
Transport Height	13’ 6” (4.1m)
Transport Width	8’ 5” (2.57 m)
Stockpile Height	41’ 3” (12.5m)
Belt	36” x 100’ (900mm x 30.9m)
Production	800 US TPH

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.

©Copyright 2019 McCloskey International. All rights reserved.
McCloskey is a trademark of McCloskey International.